

Putting Water Where it Counts!®



Valves Green Back® & Purple Back®

Made in Australia

antelco.com

Green Back® Valves

On/off device to control the water flow in low pressure irrigation systems.

Features

- Simple on/off operation and straight through flow.
- Operating pressure range up to 300 kPa.
- Green Back® cap for standard irrigation applications.
- Purple Back® lilac cap easily identifies recycled water - not for human consumption.
- UV stabilised materials for long life.



Green Back® Valve



Purple Back® Valve

Applications

End of line flushing and manual on/ off flow control of submain and lateral lines. Vineyards, orchards, nurseries, greenhouses, landscaping and home gardens.

Ordering Information - Green Back® Valves

Base type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Green Back® Valve 13 mm (Shank OD 12.6 mm)	45505	20	25	9.4
Green Back® Valve 14 mm (Shank OD 14.0 mm)	45575	20	25	9.7
Green Back® Valve 15 mm (Shank OD 14.6 mm)	45555	20	25	9.5
Green Back® Valve 16 mm (Shank OD 15.7 mm)	45515	20	24	9.9
Green Back® Valve 18 mm (Shank OD 17.6 mm)	45565	20	10	10.2
Green Back® Valve 19 mm (Shank OD 19.0 mm)	45525	20	10	10.3
Green Back® Valve 21 mm (Shank OD 20.8 mm)	45535	20	10	10.5
Green Back® Valve 25 mm (Shank OD 25.0 mm)	45545	20	4	7.1

Ordering Information - Purple Back® Valves

Base type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Purple Back® Valve 13 mm (Shank OD 12.6 mm)	46505	20	25	9.4
Purple Back® Valve 14 mm (Shank OD 14.0 mm)	46575	20	25	9.7
Purple Back® Valve 15 mm (Shank OD 14.6 mm)	46555	20	25	9.5
Purple Back® Valve 16 mm (Shank OD 15.7 mm)	46515	20	24	9.9
Purple Back® Valve 18 mm (Shank OD 17.6 mm)	46565	20	10	10.2
Purple Back® Valve 19 mm (Shank OD 19.0 mm)	46525	20	10	10.3
Purple Back® Valve 21 mm (Shank OD 20.8 mm)	46535	20	10	10.5
Purple Back® Valve 25 mm (Shank OD 25.0 mm)	46545	20	4	7.1

Specifications - Green Back® and Purple Back® Valves

		13 mm, 14 mm 15 mm, 16 mm	18 mm, 19 mm 21 mm	25 mm
UV STABILISED MATERIAL	BODY	acetal	acetal	acetal
	STEM	polypropylene	polypropylene	polypropylene
	COVER	acetal	acetal	acetal
	SEAL	-	silicone rubber	-
BASE/CONNECTION TYPE		barb	barb	barb



Threaded Valves

Threaded flow control valves for low pressure irrigation.

Features

- 1/2", 3/4" or 1" male threaded inlet.
- Simple on/off operation and straight through flow.
- Operating pressure range up to 300 kPa.
- Green Back® cap for standard irrigation applications.
- Purple Back® lilac cap easily identifies recycled water - not for human consumption.
- UV stabilised materials for long life.



Threaded Purple Back® Valve



Threaded Green Back® Valve

Applications

Irrigation from rain tanks, non-pressurised containers or pressurised systems up to 300 kPa.

Ordering Information - Green Back® Threaded Valves Male Thread

Base type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Green Back® Valve 13mm Barb x 1/2"	49005	20	22	9.8
Green Back® Valve 14mm Barb x 1/2"	49015	20	22	9.9
Green Back® Valve 15mm Barb x 1/2"	49025	20	22	9.8
Green Back® Valve 16mm Barb x 1/2"	49035	20	22	10.3
Green Back® Valve 13 mm Barb x 3/4"	46605	20	22	10.4
Green Back® Valve 14 mm Barb x 3/4"	46675	20	22	10.6
Green Back® Valve 16 mm Barb x 3/4"	46615	20	21	10.9
Green Back® Valve 18 mm Barb x 3/4"	46685	20	9	10.2
Green Back® Valve 19 mm Barb x 3/4"	46695	20	9	10.2
Green Back® Valve 21 mm Barb x 3/4"	46595	20	9	10.3
Green Back® Valve 25 mm Barb x 1"	46625	20	4	7.7

NEW

Ordering Information - Purple Back® Threaded Valves Male Thread

Base type	Order Code	Pack Quantity	Packs Per Carton	Carton (kg)
Purple Back® Valve 13 mm Barb x 1/2"	49105	20	22	9.8
Purple Back® Valve 14 mm Barb x 1/2"	49115	20	22	9.9
Purple Back® Valve 15 mm Barb x 1/2"	49125	20	22	9.8
Purple Back® Valve 16 mm Barb x 1/2"	49135	20	22	10.3
Purple Back® Valve 13 mm Barb x 3/4"	46705	20	22	10.4
Purple Back® Valve 14 mm Barb x 3/4"	46775	20	22	10.6
Purple Back® Valve 16 mm Barb x 3/4"	46715	20	21	10.9
Purple Back® Valve 18 mm Barb x 3/4"	46785	20	9	10.2
Purple Back® Valve 19 mm Barb x 3/4"	46795	20	9	10.2
Purple Back® Valve 21 mm Barb x 3/4"	46805	20	9	10.3
Purple Back® Valve 25 mm Barb x 1"	46815	20	4	7.7

NEW

Specifications - Threaded Valves

	1/2" MNPT	3/4" BSPM		1" BSPM
		13 mm, 14 mm 15 mm, 16 mm	18 mm, 19 mm 21 mm	
UV STABILISED MATERIAL	BODY STEM COVER SEAL	acetal polypropylene acetal -	acetal polypropylene acetal silicone rubber	acetal polypropylene acetal -
BASE/ CONNECTION TYPE	1/2" MNPT x barb	3/4" BSPM x barb		1" BSPM x barb



Antelco Group of Companies

LINCOLN
— Est. 1959 —
MOULDING THE FUTURE

ANTELCO®

Dawn



Antelco Australia
Antelco Pty Ltd ABN 50 008 062 708
Sales & Marketing,
Orders & Warehouse
Research & Development
PO Box 95, 131 Tolley Rd,
St Agnes SA 5097 Australia
+61 8 8334 4333
adelaide@antelco.com.au

Antelco USA
Antelco Corporation
Sales & Marketing,
Orders & Warehouse
886 Waterway Pl,
Longwood,
Florida 32750 USA
+1 407 331 0699
info@antelco.com

Antelco Europe
Antelco UK Limited
Sales & Marketing,
Orders & Warehouse
17a Chartmoor Rd,
Leighton Buzzard,
Bedfordshire LU7 4WG UK
+44 152 585 9990
orders@antelco.co.uk